


## fermacell Product Data Sheet



## fermacell Pipe Penetration Patches

for sealing around fittings and pipe penetrations

### Product

The **fermacell** Pipe Penetration Patches are made from alkaline-resistant and permanently elastic polypropylene-material for high quality watertight protection. They are part of the extensive **fermacell** sealing system with general building authority test certificate (P-5079/1926 MPA-BS).

### Application

**fermacell** Pipe Penetration Patches are designed for permanent watertight sealing in wall areas for pipe penetrations, shower and bath fittings under tiles, boards and ceramic coverings.

### Properties

- Extremely elastic and longitudinally stable
- Ageing-resistant
- Maintains a watertight seal
- Secure connections with **fermacell** Waterproofing Application and **fermacell** Flexible Tile Adhesive
- High compatibility:
  - Compatible with commercial tile adhesives and solvent-free coatings
  - Compatible with silicone sealants

### Processing

- The surface is prepared with **fermacell** Deep Primer (min. drying time 2 hours) and a single application of **fermacell** Waterproofing Application.
- The patch is then placed over the pipe opening and pressed in the freshly applied Waterproofing Application, and pressed into place (object must not be sharp-edged) and recoated with **fermacell** Waterproofing Application.
- After a drying period of at least 1 hour, the second coat of **fermacell** Waterproofing Application is applied. The application of a 3rd layer is possible, but not necessary. The dry film thickness of the Waterproofing Application is min. 0.5 mm.
- After approx. 2-3 hours, **fermacell** Flexible Tile Adhesive (or a tile adhesive pursuant to the general building authority test certificate) can be applied to the Waterproofing Application in the thin-bed process.

## fermacell Pipe Penetration Patches

for sealing fittings and pipe penetrations

### Processing information

- The drying times depend on the temperature of the air and the building, the air movement, the humidity and the absorptive capacity of the substrate. The specified drying times relate to +20 °C and a relative humidity of 50 %.
- The processing temperature should lie between +5 °C and +25 °C. Clean tools with water after use.
- Due to the wide range of possible influences during processing and application, the user should always carry out trial processing and application.

Please also observe our detailed processing instructions in our brochures and videos at [www.fermacell.com](http://www.fermacell.com)

| Material properties   |                   |
|---|-------------------|
| Dimensions  | 12 x 12 cm        |
| Material weight   | approx. 20 g/unit |
| Temperature resistance  | - 30°C to + 95°C  |
| Water impermeability  | > 1.5 bar         |
| Storage<br>(at room temperature, dry, protect from direct sunlight) | 24 months         |

| Merchant data  |               |
|----------------|---------------|
| Item number    | 79068         |
| EAN            | 4007548005104 |
| Packaging      | 2 units / box |
| Weight / pack  | approx. 100 g |
| Quantity / box | 5 packs       |
| Weight / box   | approx. 500 g |



## **fermacell** Pipe Penetration Patches

for sealing fittings and pipe penetrations

### Further information

Our recommendations are based on extensive testing and practical experiences. They do not replace guidelines, standards, approvals and applicable technical data sheets. Due to the large number of possible influences for processing and application, we recommend that you carry out trial processing and application. No claims for compensation may be derived from the information provided. Delivery, processing and the warranty on features assured by us will be in accordance with our GTCs.

[www.ecobati.com](http://www.ecobati.com)



[www.ecobati.be](http://www.ecobati.be) | [info@ecobati.be](mailto:info@ecobati.be)